

C75NMNM Test Cable

2 Foot Cable

Electrical Specifications

Frequency Range	0.3 MHz - 3 GHz
Impedance	75 Ω
Insertion Loss	0.5 dB
Return Loss	
0.3 MHz - 1 GHz	25 dB min, 35 dB typ.
1 GHz - 2 GHz	25 dB min, 30 dB typ.
2 GHz - 3 GHz	23 dB min, 28 dB typ.

Mechanical Specifications

Connector	75 Ω , type-N male & type-N male
Length	60 \pm 1 cm
Net weight (approx.)	177 g

3 Foot Cable

Electrical Specifications

Frequency Range	0.3 MHz - 3 GHz
Impedance	75 Ω
Insertion Loss	0.8 dB
Return Loss	
0.3 MHz - 1 GHz	25 dB min, 35 dB typ.
1 GHz - 2 GHz	25 dB min, 30 dB typ.
2 GHz - 3 GHz	25 dB min, 28 dB typ.

Mechanical Specifications

Connector	75 Ω , type-N male and type-N male
Length	90 \pm 1 cm
Net weight (approx)	211 g



4 Foot Cable

Electrical Specifications

Frequency Range	0.3 MHz - 3 GHz
Impedance	75 Ω
Insertion Loss	0.5 dB
Return Loss	
0.3 MHz - 1 GHz	25 dB min, 35 dB typ.
1 GHz - 2 GHz	25 dB min, 30 dB typ.
2 GHz - 3 GHz	23 dB min, 28 dB typ.

Mechanical Specifications

Connector	75 Ω , type-N male & type-N male
Length	120 \pm 1 cm
Net weight (approx.)	266 g

5 Foot Cable

Electrical Specifications

Frequency Range	0.3 MHz - 3 GHz
Impedance	75 Ω
Insertion Loss	0.5 dB
Return Loss	
0.3 MHz - 1 GHz	25 dB min, 35 dB typ.
1 GHz - 2 GHz	25 dB min, 30 dB typ.
2 GHz - 3 GHz	23 dB min, 28 dB typ.

Mechanical Specifications

Connector	75 Ω , type-N male & type-N male
Length	150 \pm 1 cm
Net weight (approx.)	310 g



C75NMFM Test Cable

2 Foot Cable

Electrical Specifications

Frequency Range	0.3 MHz - 3 GHz
Impedance	75 Ω
Insertion Loss	0.5 dB
Return Loss	at 50 Ω port:
0.3 MHz - 1 GHz	25 dB min, 35 dB typ.
1 GHz - 2 GHz	25 dB min, 30 dB typ.
2 GHz - 3 GHz	23 dB min, 28 dB typ.

Mechanical Specifications

Connector	75 Ω , type-N male & type-F male
Length	60 \pm 1 cm
Net weight (approx.)	145 g



3 Foot Cable

Electrical Specifications

Frequency Range	0.3 MHz - 3 GHz
Impedance	75 Ω
Insertion Loss	0.7 dB
Return Loss	
0.3 MHz - 1 GHz	25 dB min, 35 dB typ.
1 GHz - 2 GHz	25 dB min, 30 dB typ.
2 GHz - 3 GHz	23 dB min, 28 dB typ.

Mechanical Specifications

Connector	75 Ω , type-N male and type-F male
Length	90 \pm 1 cm
Net weight (approx)	162 g

4 Foot Cable

Electrical Specifications

Frequency Range	0.3 MHz - 3 GHz
Impedance	75 Ω
Insertion Loss	0.9 dB
Return Loss	at 50 Ω port:
0.3 MHz - 1 GHz	25 dB min, 35 dB typ.
1 GHz - 2 GHz	25 dB min, 30 dB typ.
2 GHz - 3 GHz	23 dB min, 28 dB typ.

Mechanical Specifications

Connector	75 Ω , type-N male and type-F male
Length	120 \pm 1 cm
Net weight (approx)	185 g

